

AsiaPower UPS AP1026

Power Backup + Protection

Give Protection from Power impurities.
Save your work & equipment when Power goes.



- Line interactive design
- Fully digitized microprocessor controlled
- AVR input voltage Range 145V- 275V
- Off mode Battery charging
- Boost and buck AVR (Auto voltage regulation)
- Cold start function (DC power on)
- Short circuit and overload protection
- Advanced battery management (ABM technology)

Model	AP 1026	
Capacity	1000VA/600W	
Input	Voltage	230V
	Frequency Range	45-55Hz
	AVR	145V-275V
	Connection (1.5m wire)	3 pin 6A, Indian plug
Output	Voltage on mains	230V + 10% - 15%
	Frequency on mains	Follows input
	Voltage on Battery	230V ± 5%
	Waveform	Quasi sinewave
	Power Factor Lagging	0.6
	Efficiency	> 78%
	Sockets	4 x universal sockets
Protection	Input Protection	MCB / Fuse
	O/P short circuit	UPS shutdown immediately
	O/P overload shutdown	110% for 3 min, 150% for 10 Sec
Transfer Time	Mains to Inverter	4 - 8 ms
Battery	DC Bus	24V
	Battery charger	2.5A / 4.5A selectable
	Life	2-3 years typical lifetime
	External Battery	SMF Battery Pack, 2x26AH
	Protection	Auto discharge protection
	Typical Recharging time	Depends on Load
Backup Time	3 hours on 1 PC load	
Indications	Power ON	Green LED
	Inverter ON	Red LED
	Battery charging	Yellow LED
Alarm	Battery backup	Slow beeping sound (about 0.47Hz)
	Battery Low	Rapid beeping sound (about 1.8 Hz)
	Overload	Continuous beeping sound
Environment	Ambient operation	0-40°C, 0-95% humidity non condensing, 3500 meter max.
	Audible noise	< 40 DbA (1 meter from surface)
	Storage Condition	15,000 meter max. Elevation
Physical	Weight	18.5 Kgs.
	Dimension - DxWxH (mm)	45 x 370 x 211

Specification subject to change without prior intimation

AsiaPower

keeping your technology alive

UPS with Long Backup - Plug & Play - 1 year warranty